

Standard 1.2 W 12 V W2x4.6d



Product family benefits

- Suitable for the most common signal and interior applications
- Affordable
- Reliable manufacturer
- For good visibility
- Reliable products

Product family features

- Broad product range
- Good quality thanks to German technology
- Lamps for exterior applications are ECE certified
- Normed light output
- Basis for good light distribution

Areas of application

- Position and parking light
- Indicator, brake, fog and reversing lights
- Number plate and side position lights
- Interior lighting and reading lights
- Instrument and switch lighting



N286

Electrical data

Power input	1.22 W
Test voltage	13.5 V
Power input tolerance	±15 %
Nominal wattage	1.20 W
Nominal voltage	12.0 V

Photometrical data

Luminous flux	7.5 lm
Luminous flux tolerance	±20 %

Dimensions & weight

Diameter	5 mm
Product weight	0.40 g
Length	20.0 mm

Lifespan

Lifespan Tc	1500 h
Lifespan B3	500 h

Additional product data

Base (standard designation)	W2x4.6d
-----------------------------	---------

Certificates & standards

British standard	286
------------------	-----

Logistical data

Order reference	N286
-----------------	------

Packaging Information

Packaging description NEOLUX	EAN	Packaging type	Amount of article
N286	4008321770653	Folding box	10
N286S	4008321771049	Folding box	1



