



NEOLUX®
GERMAN TECHNOLOGY

LED Exterior 6000 K 38.2 mm BA15S

NEOLUX LED retrofits transform vehicle exteriors with modern, cold white light. NEOLUX LED retrofits replace most traditional white auxiliary lamps with ease. The results are more than aesthetic. In addition to that, the long-lasting, affordable NEOLUX LED lamps use less energy than conventional lamps. With a color temperature of 6,000 K, NEOLUX has the ideal solution for upgrading the exterior appearance of your vehicle.



NP2160CW-02B

Product family benefits

- Upgrade with the latest LED technology
- Modern look
- Better visibility
- Homogeneous illumination thanks to modern diffuser optics
- Longer replacement cycle

Product family features

- Contemporary, cold white color temperature with 6,000 K
- High brightness
- Even light distribution
- Ideal fit thanks to compact dimensions
- Long lifetime

Areas of application

- Exterior lighting




NP2160CW-02B

Product information	
Product type (off-road vs. on-road)	Off-road
Application (Category and Product specific)	Mainly used for signal/ indicator applications
Electrical data	
Power input	1.44 W
Test voltage	13.5 V
Power input tolerance	±20 %
Nominal wattage	1.20 W
Nominal voltage	12.0 V
Photometrical data	
Color temperature	6000 K
Luminous flux	85 lm
Luminous flux tolerance	±20 %
Light color LED	Cool white
Dimensions & weight	
Diameter	20.0 mm
Product weight	12.02 g
Length	38.2 mm
Lifespan	
Lifespan Tc	2000 h
Lifespan B3	2000 h
Additional product data	
Base (standard designation)	BA15s
Capabilities	
Technology	LED
Certificates & standards	
ECE category	≡ P21W
Logistical data	
Order reference	NP2160CW-02B
Environmental information	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899477414 4052899477438 4052899620049 4062172182805
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	27e306e9-8de2-47ea-b54f-4493ab032e80 a106977a-d26b-459d-ac3e-decfc82d1265 5e5d52b7-41c0-4563-99dd-9ddc5b5d638c

e7dccdef-fca5-406c-
9c69-489ff3d1efd9

Packaging Information

Packaging description	EAN	Packaging type	Amount of article
NEOLUX			
NP2160CW-02B	4052899477438	Blister	2



Legal advice

These products do not have ECE approval. This means they must not be used on public roads in any exterior application. Use on public roads leads to cancellation of operating license and loss of insurance coverage. Several countries do not allow sale and use of these products. Please contact your local distributor for information on the availability in your country.

NEOLUX[®]
GERMAN TECHNOLOGY

NEOLUX Automotive Lighting
OSRAM GmbH

www.neolux-lighting.com

Marcel-Breuer-Str 4
80807 Munich, Germany

Phone +49 89 6213-0
Fax +49 89 6213-2020