



NEOLUX®
GERMAN TECHNOLOGY

LED Headlamp 6500 K 58.0 mm PX26d

Thanks to a very compact socket design, these new lamps allow a high compatibility and an easy installation. The pair of lamps comes with a color temperature of 6 500 K – providing a stylish upgrade with Cool White LED light and a superior brightness. The latest LED technology guarantees a long service life.







N499DWBS-2SCB



N499DWBS-2SCB

Product information	
Product type (off-road vs. on-road)	Off-road ≙ H7/H18
Application (Category and Product specific)	Headlights

Electrical Data	
Test voltage	13.2 V
Nominal wattage	11 W
Nominal voltage	12 V

Photometric Data	
Color temperature	6500 K
Nominal luminous flux	1100 lm
Luminous flux tolerance	±25 %
Light color LED	Cool white

Physical Attributes & Dimensions	
Diameter	13.5 mm
Diameter	13.5 mm
Product weight	24.00 g
Length	58.0 mm
Lamp base	-

Capabilities	
Technology	LED

Certificates & standards	
ECE category	≙ H7/H18

Environmental & Regulatory Information	
Primary article identifier	4062172316361 4062172326261
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	e9a530ea-7f03-4860-ad63-cb2f3b933d21 7df39c1d-6889-4887-895a-f7ba42c0d5f5

Packaging Information			
Packaging description	EAN	Packaging type	Amount of article
NEOLUX			
N499DWBS-2SCB	4062172326261	SOFT COVER BOX	2

Legal advice

These products do not have ECE approval. This means they must not be used on public roads in any exterior application. Use on public roads leads to cancellation of operating license and loss of insurance coverage. Several countries do not allow sale and use of these products. Please contact your local distributor for information on the availability in your country.



www.neolux-lighting.com

NEOLUX Automotive Lighting
OSRAM GmbH

Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

Marcel-Breuer-Str 4
80807 Munich, Germany

Phone +49 89 6213-0
Fax +49 89 6213-2020